


100-10468-1030



**Fig. 1**




Fig. 2

[illegible]

Fig. 3

TOBOTT" 8940700T

Gauge: 14  
 Needles: 24  
 Thread-guides: 44  
 Eyelets: 0  
 Bars: 4  
 Links: 48

Take-down rollers	A: 0	B: 0
AL.3R	C: 0	D: 0
AL.3RDF/AL.3RS	E: 0	F: 0
AL.POS/C	G: 0	H: 0

Stitches per cm: 30 Elasticity: 0

Elastic threads Type Tuntex Poly Count Total: 0  
 Warp threads Type Tuntex Poly Count 1/150 Total: 24


West Threads	Type	Count	Thread-guides	Threads per thread-guide	Total
Bar 1:	Tuntex Poly	1/150	21	1	21
Bar 2:	Tuntex Poly	1/150	21	1	21
Bar 3:	Flat Bright Poly Dillion	1/150/48 100% Poly Bright A.D.	1	3	3
Bar 4:	Tuntex Poly	1/150	1	5	5

Machine: 407  
 RPM: 1000  
 Needle grooves: 221  
 Performance coefficient: 0.85  
 Bands obtainable contemporaneously: 7  
 Hourly production rate per band (m): 17.00  
 Total hourly production (m): 119.00

Notes  
 Stitches equals picks. Run bright poly, each end separated in reed.

Fig. 4

10010168-110801



**Fig. 5**

[illegible]

Fig. 7





Fig. 6

3100101031001



**Fig. 8**





Fig. 9